

Min. Pulley Dia.	Wire Diameter		Belt Thickness												
			Up to 3/64" .047"	1/16" .063"	3/32" .093"	1/8" .125"	5/32" .156"	3/16" .188"	7/32" .219"	1/4" .250"	9/32" .281"	5/16" .313"	11/32" .344"	25/64" .390"	
	in.	mm	1.2 mm	1.6 mm	2.4 mm	3.2 mm	4.0 mm	4.8 mm	5.6 mm	6.4 mm	7.1 mm	7.9 mm	9.0 mm	10.0 mm	
15/16" 24 mm	.025	0.6	25SP*												
	.025	0.6	25*												
	.036 x .027	0.9 x 0.7	UCM36SL XSP												
	.036 x .027	0.9 x 0.7		UCM36SL SP											
	.025	0.6		25LP*											
2" 51 mm	.036 x .027	0.9 x 0.7	UCM36 XSP												
	.030	0.8	30*												
	.036 x .027	0.9 x 0.7		UCM36 SP*											
	.036 x .027	0.9 x 0.7		36 SP*											
	.040	1.0		1 XSP*											
	.030	0.8	30P*												
	.040	1.0	UX1 SP*												
	.036 x .027	0.9 x 0.7		UCM36*											
	.036 x .027	0.9 x 0.7		36*											
	.040	1.0		1 SP*											
	.036 x .027	0.9 x 0.7			UCM36 LP*										
	.040	1.0			1*										
	.040	1.0			UX1*										
	.047	1.2			UA2										
	3" 76 mm	.054	1.4			U2 SP									
.054		1.4			U2										
.047		1.2			UA3										
.054		1.4			2SP										
.054		1.4			2										
3-1/2" 89 mm		.054	1.4			U3-1									
		.054	1.4			3-1									
	.054	1.4			U3-2										
	.054	1.4			3										
	.054	1.4			U3										
	.054	1.4			3 - 4½										
4" 102 mm	.054	1.4			4-2										
	.054	1.4			4½ - 3										
	.054	1.4			4										
	.054	1.4			4					4½					
5" 127 mm	.054	1.4			U4										
	.054	1.4			5										
	.054	1.4			U5										
6" 152 mm	.054	1.4			6										
	.054	1.4			U6										
7" 175 mm	.054	1.4			7										
	.054	1.4			U7										

*Long Leg configuration is available; allow for 1" (25.4 mm) larger minimum pulley diameter.

 Unibar®  Carded